


Super Free Match

Capacity range from 42K Btu/h to 56K Btu/h can be widely used in residential house, hotel, business office and especially applicable in variable loading situation.



High efficiency



Intelligent Defrosting



Comprehensive protection



Compact design



Easier maintainability



Inner groove copper



'Turbo' Button



Self-Diagnosis



Low voltage startup



Timer



Lock



Wide operation range



Memory function



Wide voltage range



Centralized control



Weekly timer



Long-distance monitoring

Features: Standard Optional

- Power supply startup delay design, lower the unit starting current.
- High efficiency thanks to DC inverter compressor.
- The lowest noise thanks to advanced technology.
- The system could run stably under hard operation conditions.
- Connection pipe up to 145 meter length that convenient on installation.

RDSW**MP3XL

Item	Nominal operating condition(temperature)				Operation range(temperature)	
	Outdoor condition		Indoor condition			
	DB(°C)	WB(°C)	DB(°C)	WB(°C)		
Cooling	35	24	27	19	-15~48	
Heating	7	6	20	15	-20~24	

RDSW**MN3WL

Item	Nominal operating condition(temperature)				Operation range(temperature)	
	Outdoor condition		Indoor condition			
	DB(°C)	WB(°C)	DB(°C)	WB(°C)		
Cooling	35	24	27	19	18~48	
Heating	7	6	20	15	-10~24	

163 Combinations

RDSW(42S)MP3XL (2 to 6)	Two units	Three units		Four units		Five units		Six units
	7+18	7+7+7	7+18+24	9+21+24	7+7+7+7	7+7+18+21	7+12+18+18	7+7+7+7+7
	7+21	7+7+9	7+21+21	12+12+12	7+7+7+9	7+7+18+24	9+9+9+9	7+7+7+7+9
	7+24	7+7+12	7+21+24	12+12+18	7+7+7+12	7+9+9+9	9+9+9+12	7+7+7+7+12
	9+12	7+7+18	7+24+24	12+12+21	7+7+7+18	7+9+9+12	9+9+9+18	7+7+7+12+21
	9+18	7+7+21	9+9+9	12+12+24	7+7+7+21	7+9+9+18	9+9+9+21	7+7+7+7+21
	9+21	7+7+24	9+9+12	12+18+18	7+7+7+24	7+9+9+21	9+9+9+24	7+7+7+7+24
	9+24	7+9+9	9+9+18	12+18+21	7+7+9+9	7+9+9+24	9+9+12+12	7+7+7+9+9
	12+12	7+9+12	9+9+21	12+18+24	7+7+9+9	7+9+12+12	9+9+12+18	7+7+7+9+12
	12+18	7+9+18	9+9+24	12+21+21	7+7+9+12	7+9+12+18	9+9+12+21	7+7+7+9+9
	12+21	7+9+21	9+12+12	—	7+7+9+18	7+9+12+21	9+9+12+24	7+7+7+9+9+12
	12+24	7+9+24	9+12+18	—	7+7+9+21	7+9+12+24	9+9+18+18	7+7+7+9+12+12
	18+18	7+12+12	9+12+21	—	7+7+9+24	7+9+18+18	9+12+12+12	7+7+9+9+9
	18+21	7+12+18	9+12+24	—	7+7+12+12	7+9+18+21	9+12+12+18	7+7+9+9+12
	18+24	7+12+21	9+18+18	—	7+7+12+18	7+12+12+12	9+12+12+21	7+7+9+9+12+12
	21+21	7+12+24	9+18+21	—	7+7+12+21	7+12+12+18	12+12+12+12	7+9+9+9+9
	21+24	7+18+18	9+18+24	—	7+7+12+24	7+12+12+21	12+12+12+18	7+9+9+9+9+12
	7+18+21	9+21+21	—	7+7+18+18	7+12+12+24	—	7+7+9+9+18	9+9+9+9+9+18

288 Combinations

RDSW(48S)MP3XL (2 to 8) RDSW(48S)MN3XL (2 to 8)	Two units	Three units			Four units			
	7+18	7+7+12	9+9+9	12+18+18	7+7+7+7	7+7+21+24	7+12+12+21	9+9+18+21
	7+21	7+7+18	9+9+12	12+18+21	7+7+7+9	7+7+24+24	7+12+12+24	9+9+18+24
	7+24	7+7+21	9+9+18	12+18+24	7+7+7+12	7+9+9+9	7+12+18+18	9+9+21+21
	9+18	7+7+24	9+9+21	12+21+21	7+7+7+18	7+9+9+12	7+12+18+21	9+9+21+24
	9+21	7+9+9	9+9+24	12+21+24	7+7+7+21	7+9+9+18	7+12+18+24	9+12+12+12
	9+24	7+9+12	9+12+12	12+24+24	7+7+7+24	7+9+9+21	7+12+21+21	9+12+12+18
	12+12	7+9+18	9+12+18	18+18+18	7+7+9+9	7+9+9+24	7+12+21+24	9+12+12+21
	12+18	7+9+21	9+12+21	18+18+21	7+7+9+12	7+9+12+12	7+18+18+18	9+12+12+24
	12+21	7+9+24	9+12+24	18+18+24	7+7+9+18	7+9+12+18	7+18+18+21	9+12+18+18
	12+24	7+12+12	9+18+18	18+21+21	7+7+9+21	7+9+12+21	7+9+9+9	9+12+18+21
	18+18	7+12+18	9+18+21	18+21+24	7+7+9+24	7+9+12+24	9+9+9+12	9+12+18+24
	18+21	7+12+21	9+18+24	21+21+21	7+7+12+12	7+9+18+18	9+9+9+18	9+12+21+21
	18+24	7+12+24	9+21+21	—	7+7+12+18	7+9+18+21	9+9+9+21	9+18+18+18
	21+21	7+18+18	9+21+24	—	7+7+12+21	7+9+18+24	9+9+9+24	12+12+12+12
	21+24	7+18+21	9+24+24	—	7+7+12+24	7+9+21+21	9+9+12+12	12+12+12+18
	24+24	7+18+24	12+12+12	—	7+7+18+18	7+9+21+24	9+9+12+18	12+12+12+21
	—	7+21+21	12+12+18	—	7+7+18+21	7+9+24+24	9+9+12+21	12+12+12+24
	—	7+21+24	12+12+21	—	7+7+18+24	7+12+12+12	9+9+12+24	12+12+18+18
	—	7+24+24	12+12+24	—	7+7+21+21	7+12+12+18	9+9+18+18	12+12+18+21

Six units				
7+7+7+7+7+7	7+7+7+9+12+12	7+7+9+9+12+18	7+9+9+12+12+18	12+12+12+12+12+12
7+7+7+7+7+9	7+7+7+9+12+12	7+7+9+9+12+21	7+9+9+12+12+21	-
7+7+7+7+7+12	7+7+7+9+12+18	7+7+9+9+12+24	7+9+12+12+12+12	-
7+7+7+7+7+18	7+7+7+9+12+21	7+7+9+9+18+18	7+9+12+12+12+18	-
7+7+7+7+7+21	7+7+7+9+12+24	7+7+9+9+18+21	7+12+12+12+12+12	-
7+7+7+7+7+24	7+7+7+9+18+18	7+7+9+12+12+12	9+9+9+9+9+9	-
7+7+7+7+9+9	7+7+7+9+18+21	7+7+9+12+12+18	9+9+9+9+9+12	-
7+7+7+7+9+12	7+7+7+9+18+24	7+7+9+12+12+21	9+9+9+9+9+18	-
7+7+7+7+9+18	7+7+7+9+21+21	7+7+9+12+12+24	9+9+9+9+9+21	-
7+7+7+7+9+21	7+7+7+12+12+12	7+7+9+12+18+18	9+9+9+9+9+24	-
7+7+7+7+9+24	7+7+7+12+12+18	7+9+9+9+9+9	9+9+9+9+12+12	-
7+7+7+7+12+12	7+7+7+12+12+21	7+9+9+9+9+12	9+9+9+9+12+18	-
7+7+7+7+12+18	7+7+7+12+12+24	7+9+9+9+9+18	9+9+9+9+12+21	-
7+7+7+7+12+21	7+7+7+12+18+18	7+9+9+9+9+21	9+9+9+9+12+24	-
7+7+7+7+12+24	7+7+7+12+18+21	7+9+9+9+9+24	9+9+9+9+18+18	-
7+7+7+7+18+18	7+7+9+9+9+9	7+9+9+9+12+12	9+9+9+12+12+12	-
7+7+7+9+9+9	7+7+9+9+9+12	7+9+9+9+12+18	9+9+9+12+12+18	-
7+7+7+9+9+12	7+7+9+9+9+18	7+9+9+9+12+21	9+9+9+12+12+21	-
7+7+7+9+9+18	7+7+9+9+9+21	7+9+9+9+12+24	9+9+12+12+12+12	-
7+7+7+9+9+21	7+7+9+9+9+24	7+9+9+9+18+18	9+9+12+12+12+18	-
7+7+7+9+9+24	7+7+9+9+12+12	7+9+9+9+12+12	9+12+12+12+12+12	-

RDSW(56S)MP3XL
(2 to 9)
RDSW(56S)MN3WL
(2 to 9)



Outdoor Unit

Model	Heat Pump		RDSW(42S)MP3XL	RDSW(48S)MP3XL	RDSW(48S)MN3WL	RDSW(56S)MP3XL	RDSW(56S)MN3WL
Capacity	Cooling	Btu/h	42000	47800	47800	52900	54600
	Heating	Btu/h	42700	53000	54600	59700	61400
Power supply		Ph/V/Hz	1/220~240/50	1/220~240/50	3/380~415/50	1/220~240/50	3/380~415/50
	Cooling	kW	4.10	4.90	4.60	5.30	5.20
Power input	Heating	kW	3.70	4.30	4.25	4.80	4.70
	Refrigerant charge volume	kg	4.95	4.95	4.95	4.95	4.95
Air Pressure Level		m³/h	6400	6400	6600	7000	6600
Sound pressure level		dB(A)	55	55	58	58	58
Dimension(W×D×H)	Outline	mm	900×340×1345	900×340×1345	900×340×1345	900×340×1345	900×340×1345
	Package	mm	993×453×1500	993×453×1500	993×453×1500	993×453×1500	993×453×1500
Net weight/Gross weight		kg	116/125	116/125	121/132	116/125	121/132
Connecting pipe diameter	Gas	inch(mm)	φ5/8(15.9)	φ5/8(15.9)	φ16	φ5/8(15.9)	φ19
	Liquid	inch(mm)	φ3/8(9.52)	φ3/8(9.52)	φ9.52	φ3/8(9.52)	φ9.52
Max. equivalent connection pipe length		m	115	135	135	145	145
Maximum drive IDU NO.		unit	6	8	8	9	9
Loading quantity	40'GP/40'HQ	sets	50/50	50/50	50/50	50/50	50/50

1.The product with * is under development, and the parameters are estimated, please refer to the value on nameplates.

2. Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales representatives.

BU Module

Model		UCZ2Z-P	UCZ2Y-P	UCZ3Z-P	UCZ3Y-P	UCY3Z-P	UCY5Z-P
Fuse current	A	3.15	3.15	3.15	3.15	3.15	3.15
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50	1/220~240/50	1/220~240/50	1/220~240/50
Dimension(WxDxH)	Outline	mm	361×313×182	361×313×182	361×313×182	513×312×193	513×312×193
	Package	mm	683×392×258	683×392×258	683×392×258	676×473×268	676×473×268
Connection Method	—	Flare	Braze	Flare	Braze	Flare	Flare
Net weight/Gross weight	kg	6.5/8.3	6.5/8.3	7.0/9.0	7.0/9.0	8.0/10.0	9.0/11.0
Connecting pipe diameter (to IDU)	Gas	inch(mm)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)
	Liquid	inch(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)
Connecting pipe diameter (to ODU)	Gas	inch(mm)	Φ5/8(15.9)	Φ5/8(15.9)	Φ5/8(15.9)	Φ5/8(15.9)	Φ5/8(15.9)
	Liquid	inch(mm)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)
Maximum connect IDU NO.	unit	2	2	3	3	3	5
Loading quantity	40'GP	sets	294	294	294	246	246
	40'HQ	sets	294	294	294	246	246
Max. Equivalent	m	15	15	15	15	15	15

Wall Mounted Indoor Unit

Emraude



Model	RDS(07)GZ-P3WMZ1V/R	RDS(09)GZ-P3WMZ1V/R	RDS(12)GY-P3WMZ1V/R	RDS(18)GX-P3WMZ1V/R
Capacity	Cooling Btu/h	7165	8530	11942
	Heating Btu/h	8871	9383	12454
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50
Airflow volume	(m ³ /h) (SH/H/M/L)	550/490/370/290	550/490/370/290	770/670/530/410
	CFM (SH/H/M/L)	324/288/218/171	324/288/218/171	430/394/312/241
Sound pressure level	dB(A)/SH/H/M/L	41/36/34/32/28/24/21	41/36/34/32/28/24/21	43/36/34/32/28/24/21
Connecting pipe	Gas inch(mm)	Φ3/8(9.52)	Φ3/8(9.52)	Φ1/2(12.7)
	Liquid inch(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)
Dimension(WxDxH)	Outline mm	806×209×292	806×209×292	866×209×292
	Package mm	888×297×377	888×297×377	945×297×377
Net weight/Gross weight	kg	10.5/13.0	10.5/13.0	11.0/13.5
Loading quantity	20'GP sets	266	266	252
	40' GP/40' HQ sets	553/632	553/632	518/592
				366/427

Rubis



Model	RDS07JZ-P3WMZ5X/R	RDS09JY-P3WMZ1T/R	RDS12JX-P3WMZ1T/R	RDS18JW-P3WMZ1T/R	RDS24JV-P3WMZ1T/R
Capacity	Cooling Btu/h	7506	8871	12000	17500
	Heating Btu/h	7848	9600	12500	18000
Power Supply	Ph,V,Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz
Airflow Volume	Indoor m ³ /h	500/420/390/300	560/490/430/330	660/540/460/330	800/720/610/520
Sound Power Level	Indoor dB(A)/SH/H/M/L	40/36/34/24	55/52/44/38	57/53/45/42	58/54/51/48
Outline Dimension	WxHxD mm	713×270×195	790×275×200	845×289×209	970×300×224
Package Dimension	WxHxD mm	776×268×362	866×367×271	921×379×281	1041×383×320
Net Weight/Gross Weight	Indoor kg	8.5/10	9/11	10/12	13.5/16.5
Piping Connection	Gas inch(mm)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)	Φ1/2(12.7)
	Liquid inch(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)
Loading Quantity	40'GP sets	299	223	210	127
	40'HQ sets	328	256	244	146
					131

Saphir



Model	RDS(07)NZ-P3WMZ3V/R	RDS(09)NZ-P3WMZ3V/R	RDS(12)NY-P3WMZ3V/R	RDS(18)NX-P3WMZ3V/R
Capacity	Cooling Btu/h	7500	8900	11900
	Heating Btu/h	8900	9600	13000
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50
Airflow volume	(m ³ /h) (SH/H/M/L)	450/410/380/320	500/410/380/320	630/500/420/350
	CFM(SH/H/M/L)	265/241/224/188	294/241/224/188	371/295/247/206
Sound pressure level	dB(A)/SH/H/M/L	36/34/31/28/-	37/34/31/28/-	38/34/32/30/-
Connecting pipe	Gas inch(mm)	Φ3/8(9.52)	Φ3/8(9.52)	Φ3/8(9.52)
	Liquid inch(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)
Dimension(WxDxH)	Outline mm	790×170×265	790×170×265	845×180×275
	Package mm	873×370×251	873×370×251	918×370×258
Net weight/Gross weight	kg	9.0/11.0	9.0/11.0	10/12.5
Loading quantity	20'GP sets	348	348	336
	40' GP/40' HQ sets	732/852	732/852	684/798
				541/609

Topaze



Model	RDS(07)IZ-P3WMZ3V/R	RDS(09)IZ-P3WMZ3V/R	RDS(12)IY-P3WMZ3V/R	RDS(18)IX-P3WMZ3V/R	RDS(24)IX-P3WMZ3V/R
Capacity	Cooling	Btu/h	7200	8900	11900
	Heating	Btu/h	8900	9600	13000
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50	1/220~240/50
Airflow volume	m³/h(CFM)	500/420/400/300 294/247/235/177	500/420/400/300 294/247/235/177	630/530/430/320 371/312/253/194	850/780/650/500 500/459/383/294
Sound pressure level	dB(A)(SH/H) inch(mm)	40/37/35/32/- Φ3/8(9.52)	40/37/35/32/- Φ3/8(9.52)	42/39/36/33/- Φ3/8(9.52)	45/42/37/33/- Φ1/2(12.7)
Connecting pipe	Gas Liquid	inch(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)
Dimension(WxHxD)	Outline	mm	794×186×265	794×186×265	848×189×274
	Package	mm	873×258×365	873×258×365	926×371×267
Net weight/Gross weight	kg	9.0/11.5	9.0/11.5	10/12.5	13.0/16.0
Loading quantity	20'GP	sets	348	348	306
	40' GP/40' HQ	sets	720/840	720/840	636/740
					541/609
					430/491



Duct Type Indoor Unit

Model	RUS(09)VZ-P3WMZ1Z/R	RUS(12)VZ-P3WMZ1Z/R	RUS(18)VZ-P3WMZ1Z/R	RUS(21)VZ-P3WMZ1Z/R	RUS(24)VZ-P3WMZ1Z/R
Capacity	Cooling	Btu/h	8530	11940	17060
	Heating	Btu/h	9550	13140	18770
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50	1/220~240/50
Airflow volume	m³/h(CFM)	450 265	500 294	700 412	1000 588.5
Sound pressure level (H/L)	dB(A)	37/31	39/32	41/33	42/34
Connecting pipe	Gas Liquid	inch(mm)	Φ3/8(9.52) Φ1/4(6.35)	Φ3/8(9.52) Φ1/4(6.35)	Φ1/2(12.7) Φ1/4(6.35)
Dimension(WxHxD)	Outline	mm	700×615×200	700×615×200	900×615×200
	Package	mm	893×743×305	893×743×305	113×743×305
Net weight/Gross weight	kg	22/27	23/29	27/36	31/41
Loading quantity	20'GP	sets	108	108	90
	40' GP/40' HQ	sets	234/234	234/234	180/180
					162/162
					162/162



Cassette Type Indoor Unit

Model	RPS(12)YZ-P3WMZ2Z/R	RPS(18)YZ-P3WMZ2Z/R	RPS(12)YZ-P3WMZ1Z/R	RPS(18)YZ-P3WMZ1Z/R	
Capacity	Cooling	Btu/h	11942	15354	11942
	Heating	Btu/h	13648	17060	13136
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50	1/220~240/50
Airflow volume	m³/h(CFM)	600 353	600 353	680 400	680 400
Sound pressure level (SH/H/MH/MML/SL)	dB(A)	46/44/42	46/44/42	37/35/33	37/35/33
Connecting pipe	Gas Liquid	inch(mm)	Φ3/8(9.52) Φ1/4(6.35)	Φ1/2(12.7) Φ1/4(6.35)	Φ3/8(9.52) Φ1/4(6.35)
Main Body	Dimension (WxHxD)	Outline Package	mm mm	570×570×230 851×731×325	570×570×230 851×731×325
	Net weight/Gross weight	kg	18.0/23.0	18/23	25.0/33.0
Panel	Dimension (WxHxD)	Outline Package	mm mm	650×650×50 733×673×117	650×650×50 733×673×117
	Net weight/Gross weight	kg	2.5/3.5	2.5/3.5	6.5/10
Loading quantity	20'GP	sets	102	102	48
	40' GP/40' HQ	sets	209/246	209/246	128/144
					128/144
					108/128



Floor Ceiling Type Indoor Unit

Model	RGS(09)YZ-P3WMZ1Z/R	RGS(12)YZ-P3WMZ1Z/R	RGS(18)YZ-P3WMZ1Z/R	RGS(24)YZ-P3WMZ1Z/R
Capacity	Cooling	Btu/h	8530	11942
	Heating	Btu/h	9556	13136
Power supply	Ph/V/Hz	1/220~240/50	1/220~240/50	1/220~240/50
Airflow volume	m³/h(CFM)	650 382.5	650 382.5	950 559
Sound pressure level (SH/H/MH/MML/SL)	dB(A)	40/38/36	40/38/36	45/42/40
Connecting pipe	Gas Liquid	inch(mm)	Φ3/8(9.52) Φ1/4(6.35)	Φ3/8(9.52) Φ1/4(6.35)
Dimension(WxHxD)	Outline Package	mm mm	1220×700×225 1343×823×315	1220×700×225 1343×823×315
	Net weight/Gross weight	kg	40/50	40/50
Loading quantity	20'GP	sets	66	66
	40' GP/40' HQ	sets	132/132	132/132
				66
				132/132

Console



Model	RVS(09)ZZ-P3WMZ1X/R		RVS(12)ZZ-P3WMZ1X/R	RVS(18)ZZ-P3WMZ1X/R
Capacity	Cooling Heating	Btu/h Btu/h	8700 9600	11900 13000
Power supply		Ph/V/Hz	1/220~240/50	1/220~240/50
Airflow volume		m³/h CFM	500 294	600 353
Sound pressure level (SH/H/MH/M/ML/L/SL)		dB(A)	40/38/36/33/30/27/25	42/40/38/37/35/32/27
Connecting pipe	Gas Liquid	inch(mm)	Φ3/8(9.52) Φ1/4(6.35)	Φ3/8(9.52) Φ1/4(6.35)
Dimension(WxHxD)	Outline Package	mm	700×215×600 791×286×710	700×215×600 791×286×710
Net weight/Gross weight		kg	15/18 168	15/18 168
Loading quantity	20'GP 40' GP/40' HQ	sets	348/440	348/440

1. The product with * is under development, and the parameters are estimated, please refer to the value on nameplates.
 2. Gree reserves the right to modify the specifications without prior notice. Please confirm the final specifications with sales representatives.

Control System Lineup

Controlling system	Product series	Wall-mounted type				Duct type	Cassette type	Floor ceiling type	Console type
		Rubis	Emraude	Saphir	Topaze				
Wireless remote controller	BZZ1UY1								
	BG1U(MOTO)								
	BZT1UY								
	BY1U2(XFAN)								
	BZM1U1(XFAN)								
Wired controller	CP19								
Centralized controller	XV50-24/V								

Note: ● means standard, ● means optional.